

WHAT IS CLAIMED IS:

- 1 1. A flash memory with a NOR-gate architecture, comprising:
 - 2 a) A data block allocated to storage of erase and write times for other data blocks in the
3 flash memory.
- 4
- 1 2. The memory of claim 1 wherein the processor is in communication with a host computer.
- 2
- 1 3. The memory of claim 2 wherein the host computer is a dedicated Internet device.
- 2
- 1 4. The memory of claim 1 wherein the table is also operable to provide a total number of
2 bytes for each storage operation.
- 3
- 1 5. The memory of claim 1 wherein the table is also operable to provide a number of erasures
2 for each block.
- 3
- 1 6. A method of managing NOR-gate architecture flash memory, the method comprising:
 - 2 a) designating a table block of the flash memory operable to store erase and write times
3 for each block of the flash memory;
 - 4 b) creating a most recent table by tracking time used by each block for erase and write
5 operations;
 - 6 c) determining if the table block has enough space for the most recent table, wherein the
7 table block is erased if the table block does not have enough space; and
 - 8 d) writing the new erase and write table into the table block.
- 9

1 7. The method of claim 5, wherein the table is operable to store a number of erasures for
2 each block.

1 8. The method of claim 5, wherein the table block is determined to have enough space and
2 the new entry is written at the end of the most recent erase and write table.

1 9. The method of claim 5, wherein the table block is determined not to have enough space
2 and the new entry is written at the beginning of the table block.

1 10. The method of claim 5 further comprising storing a number of erase and write operations
2 and size of storage operations in a table header.

1 11. A method of presenting progress of erase and write operations in a NOR-gate architecture
2 flash memory to a user, the method comprising:

- 3 a) receiving a number of bytes to be stored in the flash memory;
- 4 b) determining the blocks to be used to store the number of bytes;
- 5 c) accessing a table containing erase and write times for each of the blocks to be used;
- 6 and
- 7 d) estimating the amount of time to store the number of bytes from the erase and write
- 8 times in the table.

1 12. The method of claim 10 further comprising tracking time used in erasing and writing to
2 the blocks to be used and updating the table with the time used.

1 13. The method of claim 10, wherein the table accessed depends upon information contained
2 in a table header.

3

1 14. The method of claim 10, wherein the estimated amount of time is updated and
2 communicated in an iterative fashion.

3

1 15. The method of claim 10, wherein the estimated amount of time is only communicated
2 once.

3

4

5

6